

# DDL

## 150 USB Discharger



### MAIN APPLICATIONS



### SUITABLE BATTERIES

All types

### MODELS AVAILABLE

| VAC   | CODE                    | DESCRIPTION       |
|-------|-------------------------|-------------------|
| 1x230 | <b>DDL150 USB</b>       | 2-80V (96V) 150A  |
| 1x230 | <b>DDL-120-96V USB</b>  | 2-96V (115V) 120A |
| 1x230 | <b>DDL-065-150V USB</b> | 2-150 (180V) 65A  |

120 Vac input version on demand

PRODUCT INTRO

DDL discharger is aimed for workshop operations requiring discharge of batteries from 2V to 80-96-150V (depending on model).  
The device works up to 150A discharging current and is capable of parallel setting (n.2 units, up to max. 300A or n.3 units up to max. 450A)  
Integrated digital LCD display enables a complete overview and setting of main parameters.  
USB port enables data-report available in .PDF and .XLS format.

TECHNOLOGY

|                                                             |
|-------------------------------------------------------------|
| AC mains: 1 phase 230Vac ± 10% / 50-60Hz                    |
| Battery voltage: from 2V to 80-96-150V (depending on model) |
| Discharging current: up to 150A (depending on model)        |

STANDARD EQUIPMENTS / INTERFACES

|                                                                         |
|-------------------------------------------------------------------------|
| Integrated USB door for data storage/downloading and dedicated software |
| Visualization and setting through integrated LCD display                |
| Wheels for easy transport                                               |

SAFETY FEATURES


|                                     |
|-------------------------------------|
| Operative temperature: -10 to +40°C |
|-------------------------------------|

OPTIONALS

|                                                                                                       |
|-------------------------------------------------------------------------------------------------------|
| Parallel connection up to 3 modules: up to 450A discharging current - 120 Vac input version on demand |
|-------------------------------------------------------------------------------------------------------|

MECHANICAL CHARACTERISTICS

|                    |                    |
|--------------------|--------------------|
| Dimensions (LxWxH) | 470 x 310 x 700 mm |
| Weight             | 32 kg              |



2x = 300A  
3x = 450A